

## VERSE MUD RECT 120X280

| REFERENCE      | SIZE (cm) | THICKNESS (mm) | GROUP      |
|----------------|-----------|----------------|------------|
| <b>A043877</b> | 120X280   | 6,00           | PC BIA UGL |



### DIMENSIONS AND SURFACE PROPERTIES

|                                                             |              |                                  |
|-------------------------------------------------------------|--------------|----------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | UNE-EN 14411 | It accomplished all requeriments |
|-------------------------------------------------------------|--------------|----------------------------------|

### PHYSICAL PROPERTIES

|                           |                 |                    |
|---------------------------|-----------------|--------------------|
| Water absorption capacity | EN ISO 10545-03 | < 0,5%             |
| Deep abrasion resistance  | EN ISO 10545-06 | <175               |
| Thermal shock resistance  | EN ISO 10545-09 | It stands the test |
| Frost resistance          | EN ISO 10545-12 | It stands the test |

### CHEMICAL PROPERTIES

|                                                        |                 |    |
|--------------------------------------------------------|-----------------|----|
| Resistance to acids                                    | EN ISO 10545-13 | UB |
| Resistance to alcalis                                  | EN ISO 10545-13 | UB |
| Resistance to cleaning products                        | EN ISO 10545-13 | UB |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | UB |

### ANTI-SLIP CHARACTERISTICS

|                            |                |         |
|----------------------------|----------------|---------|
| Slip resistance (Rd)       | UNE-EN 16165-C | Class 2 |
| Slip resistance (R)        | EN 16165-B     | R10     |
| Slip resistance (barefeet) | EN 16165-A     | B       |
| Slip resistance (DCOF)     | ANSI A326.3    | >0,42   |