



## WORK B COAL RECT 90X90

| REFERENCE      | SIZE (cm) | THICKNESS (mm) | GROUP     |
|----------------|-----------|----------------|-----------|
| <b>A035364</b> | 90X90     | 9,00           | PC BIA GL |

### DIMENSIONS AND SURFACE PROPERTIES

|                                                             |              |                                  |
|-------------------------------------------------------------|--------------|----------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | UNE-EN 14411 | It accomplished all requeriments |
|-------------------------------------------------------------|--------------|----------------------------------|

### PHYSICAL PROPERTIES

|                               |                 |                         |
|-------------------------------|-----------------|-------------------------|
| Water absorption capacity     | EN ISO 10545-03 | < 0,5%                  |
| Flexion resistance            | EN ISO 10545-04 | => 35 N/mm <sup>2</sup> |
| Thermal shock resistance      | EN ISO 10545-09 | It stands the test      |
| Cracking resistance           | EN ISO 10545-11 | It stands the test      |
| Frost resistance              | EN ISO 10545-12 | It stands the test      |
| Light Reflectance Value (LRV) |                 | 44                      |

### CHEMICAL PROPERTIES

|                                                        |                 |     |
|--------------------------------------------------------|-----------------|-----|
| Resistance to acids                                    | EN ISO 10545-13 | GA  |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLA |
| Resistance to cleaning products                        | EN ISO 10545-13 | GA  |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | GA  |
| Stains resistance                                      | EN ISO 10545-14 | 5   |

### ANTI-SLIP CHARACTERISTICS

|                            |            |     |
|----------------------------|------------|-----|
| Slip resistance (R)        | EN 16165-B | R10 |
| Slip resistance (barefeet) | EN 16165-A | B   |